

CLAIM AMENDMENTS:

1. (currently amended) A method for administering, by an administering center, a number of automatic door apparatuses installed at different sites, comprising the steps of:

allowing a number of automatic door apparatuses to send their respective operating information to ~~an~~ the administration center along with apparatus identification information attached thereto;

classifying, by the administration center, their respective operating information in accordance with the apparatus identification information;

storing classified operating information at the administration center; and

outputting from the administration center the stored operating information ~~depending on a calling meeting a required condition regarding the classification of the~~ information.

2. (original) The method according to Claim 1, wherein the operating information includes a result on self-diagnosis of the automatic door apparatus regarding abnormality thereof.

3. (currently amended) ~~The~~A ~~method according to Claim 2, further for~~ administering a number of automatic door apparatuses installed at different sites, comprising the steps of:

allowing a number of automatic door apparatuses to send their respective opening information to an administration center with apparatus identification information attached thereto, the operating information including a result on self-diagnosis of the automatic door apparatus regarding abnormality thereof;

classifying their respective operating information in accordance with the apparatus identification information;

storing classified operating information;

outputting the stored operating information of a required condition;

predicting a possible malfunction of the automatic door apparatus based on the stored operating information; and

outputting a result of prediction regarding the possible malfunction.

4. (currently amended) The method according to Claim 1, wherein ~~a user is accessible to the administration center by~~ is communicatively ~~connecting the administration center~~ connected with an information terminal device provided in a maintenance station which is assigned ~~for the user~~ to carry out maintenance service of the automatic door apparatus, and wherein part or all of the stored operating information is transmittable to the maintenance station in response to ~~a user's~~ request of reading out the operating information ~~through~~ from the information terminal device.

5. (currently amended) A system for administering a number of automatic door apparatuses, comprising:

a number of automatic door apparatuses each of which is provided with a sender ~~which is provided on each of a number of door apparatus to send~~ for sending operating information of its own ~~apparatus~~ with identification information attached thereto; and

an administration center ~~which receives~~ including a receiver for receiving the sent operating information and the identification information ~~of~~ from each automatic door apparatus, ~~and classifies~~ a classifier for classifying the operating information in accordance

with the apparatus identification information, and ~~stores~~ a storage for storing the classified operating information ~~for to output of~~ the stored operating information in response to a calling request.

6. (currently amended) ~~The~~A system ~~according to Claim 5, for~~
administering a number of automatic door apparatuses, comprising:

a sender which is provided on each of a number of door apparatus to send
operating information of its own apparatus with identification information attached thereto;
and

an administration center which receives the sent operating information and
the identification information of each automatic door apparatus, and classifies the
operating information in accordance with the apparatus identification information, and
stores the classified operating information for output of the stored operating information in
response to a request;

wherein the administration center is operative to predict a possible malfunction in the requested door apparatus based on the stored operating information, and the administration center includes a malfunction predicting section for outputting a ~~result on~~ of prediction regarding the possible malfunction.

7. (currently amended) The system according to Claim 5, wherein the administration center includes a search section ~~for allowing a user to make~~ making a search relating to the stored operating information under a designated condition.

8. (currently amended) The system according to Claim 5, wherein the automatic door apparatus includes a device for self-diagnosing abnormality of the automatic door apparatus, and the sender is operative to send, to the administration

center, a result-~~on~~ of the self-diagnosis with information relating to occurrence of the abnormality attached thereto when the result-~~on~~ of the self-diagnosis includes the information relating to occurrence of the abnormality.

9. (currently amended) The system according to Claim 8, ~~wherein further comprising maintenance stations, each of which includes an information terminal device communicatively connected with the administration center is communicatively connected with an information terminal device, each of the maintenance stations which is assigned for the user being adapted to carry out maintenance service of~~ for at least one of the automatic door apparatuses, and the administration center is being operative to receive from the automatic door apparatuses and send to a designated one of maintenance stations the information relating to occurrence of the abnormality and the self-diagnosis result attached thereto to the information terminal device of, the designated maintenance station being which is designated in advance based on the apparatus identification information in response to receiving the for the automatic door apparatus that sends the administration center information relating to occurrence of the abnormality and the self-diagnosis result attached thereto from the automatic door apparatus.

10. (currently amended) The A system according to Claim 9, for administering a number of automatic door apparatuses, comprising:

a sender which is provided on each of the number of door apparatuses to send operating information of its own apparatus with identification information attached thereto; and

an administration center which receives the sent operating information and the identification information of each automatic door apparatus, and classifies the

operating information in accordance with the apparatus identification information, and stores the classified operating information for output of the stored operating information in response to a request;

the automatic door apparatus including a device for self-diagnosing abnormality of the automatic door apparatus, and the sender being operative to send, to the administration center, a result on the self-diagnosis with information relating to occurrence of the abnormality attached thereto when the result on the self-diagnosis includes the information relating to occurrence of the abnormality, the administration center being communicatively connected with an information terminal device of a maintenance station which is assigned to carry out maintenance service of the automatic door apparatus, and the administration center being operative to send the information relating to occurrence of the abnormality and the self-diagnosis result attached thereto to the information terminal device of the maintenance station which is designated in advance based on the apparatus identification information for the automatic door apparatus that sends the administration center the information relating to occurrence of the abnormality and the self-diagnosis result attached thereto; and

wherein the information terminal device of the maintenance station is operative to visibly alert occurrence of the abnormality on a display section of the information terminal device along with contents ~~on~~ of the abnormality ~~in response to receiving~~ when the maintenance station receives the information relating to occurrence of the abnormality and the self-diagnosis result.

11. (currently amended) The system according to Claim 10, wherein at least one of client contact information and maintenance-agent station contact information is

displayed in terms of link or guidance on the display section.

12. (currently amended) The system according to Claim 10, wherein a history on repair of repairs that has have been carried out against abnormalities in response to the contents on the abnormality is visibly displayed on the display section.

13. (currently amended) TheA system according to Claim 9, for administering a number of automatic door apparatuses, comprising:

a sender which is provided on each of the number of door apparatuses to send operating information of its own apparatus with identification information attached thereto; and

an administration center which receives the sent operating information and the identification information of each automatic door apparatuses, and classifies the operating information in accordance with the apparatus identification information, and stores the classified operating information for output of the stored operating information in response to a request;

the automatic door apparatus including a device for self-diagnosing abnormality of the automatic door apparatus, and the sender being operative to send, to the administration center, a result on the self-diagnosis with information relating to occurrence of the abnormality attached thereto when the result on the self-diagnosis includes the information relating to occurrence of the abnormality, the administration center being communicatively connected with an information terminal device of a maintenance station which is assigned to carry out maintenance service of the automatic door apparatus, and the administration center being operative to send the information relating to occurrence of the abnormality and the self-diagnosis result attached thereto to the

information terminal device of the maintenance station which is designated in advance based on the apparatus identification information for the automatic door apparatus that sends the administration center the information relating to occurrence of the abnormality and the self-diagnosis result attached thereto; and

wherein part or all of the stored operating information, or a result on prediction of a possible malfunction is transmittable through the information terminal device of the maintenance station to the maintenance station in response to a user's request of for reading out the operating information or outputting the result ~~on~~ of prediction of the possible malfunction ~~through the information terminal device of the maintenance station.~~

14. (currently amended) An automatic door apparatus comprising:

a door ~~open/close~~ operating mechanism having a motor for opening and closing a door;

a sensor for detecting presence of an object;

a controller for driving the motor of the door ~~open/close~~ operating mechanism based on a signal outputted from the sensor to open and close the door;

an operating information extractor which extracts repeatedly at intervals, from the controller, operating information of the automatic door apparatus including a sensor state information indicating a detected state of the sensor and a door state information indicating an open/close control state of the door, ~~as operating information of the automatic door apparatus~~, the door state information being cooperatively associated with the sensor state information; and

a memory device which time-sequentially stores the operating information repeatedly extracted by the extractor ~~in time series~~.

15. (currently amended) The apparatus according to Claim 14, wherein the operating information includes signal information which is communicable between the controller and an external apparatus electrically ~~connectable~~ connected with the controller.

16. (currently amended) The apparatus according to Claim 14, wherein the automatic door apparatus function of self-diagnosing malfunction or abnormality of the automatic door apparatus with the sensor or its equivalent while storing a result ~~on~~ of the self-diagnosis in a memory, and the extractor is operative to extract the self-diagnosis result from the memory as the operating information for storing the self-diagnosis result in the memory device in time-series.

17. (original) The apparatus according to Claim 14, further includes a monitor which monitors a malfunction, and the extractor extracts an operation history of the automatic door apparatus from the controller for storage in the memory device.

18. (original) The apparatus according to Claim 14, wherein the extractor extracts an altered designated value when the designated value set in the automatic door apparatus is altered for storage in the memory device.

19. (currently amended) ~~The~~ An automatic door apparatus ~~according to Claim 14, comprising:~~

a door open/close mechanism having a motor for opening and closing a door;

a sensor for detecting an object;

a controller for driving the motor of the door open/close mechanism based on a signal outputted from the sensor to open and close the door;

an operating information extractor which extracts, from the controller, a

sensor state information indicating a detected state of the sensor and a door state information indicating an open/close control state of the door, as operating information of the automatic door apparatus, the door state information being cooperatively associated with the sensor state information; and

a memory device which sequentially stores the operating information extracted by the extractor in time-series, wherein the extractor updates contents stored in the memory device at a predetermined cycle.

20. (currently amended) ~~The~~An automatic door apparatus according to Claim 14 comprising:

a door open/close mechanism having a motor for opening and closing a door;

a sensor for detecting an object;

a controller for driving the motor of the door open/close mechanism based on a signal outputted from the sensor to open and close the door;

an operating information extractor which extracts, from the controller, a sensor state information indicating a detected state of the sensor and a door state information indicating an open/close control state of the door, as operating information of the automatic door apparatus, the door state information being cooperatively associated with the sensor state information; and

a memory device which sequentially stores the operation information extracted by the extractor in time-series, wherein the extractor suspends overwriting of the operating information into the memory device when occurrence of malfunction is detected in the automatic door apparatus, and retains the operating information and the self-

diagnosis result before the detection of the occurrence of the malfunction in the memory device.